

SPEED DOME CAMERA DSC-2000SE



**300X ZOOM, 570TVL
TDN, 0.0007Lux**

FEATURES

- 410K Pixel, 1/4" Sony Progressive Scan CCD, 23x Automatic Focus Optical Zoom (10X Digital)
- Built-in Hitach DSP 6 Module, Day & Night (ICR)
- Min. Illumination 0.009 Lux with Built-in DSS, Perfect WDR function
- Smart Zoom (Speed control by Zoom ratio), 250 Programmable Preset Positions
- Swing, Group, Trace, Spiral, Auto Flip, Alarm, 8 Privacy Masking Zones
- Motion Detection, Weather proof(IP66)
- Suits for Factory, Military Base, Outside Building etc.

SPECIFICATIONS

MODEL	DSC-2000Se	
Signal system	NTSC	PAL
Image sensor	1/4" Sony HAD CCD	
Effective pixels	768(H) × 494(V)	752(H) × 582(V)
Horizontal resolution	More than 520 TVL, B/W 570 TVL	
Lens	30x Optical zoom, f=3.3-99mm	
Digital zoom	10x (Total zoom 300x)	
Angle of view	Approx 58.17°(Wide), Approx 2.2°(Tele)	
Minimum illumination	0,7 Lux, 0,1Lux(D&N), Min 0,0007Lux(DSS) / F1,6	
Luminance S/N ratio	More than 50dB	
Video output	1 Vp-p Composite video output 75Ω	
Focus mode	Auto / Manual / Oneshot	
SSNR	Off / Low / Middle / High	
Back light	Off / Low / Middle / High	
Shutter speed	Auto / 1/120 ~ 1/60,000 sec	
Sharpness control	Level (0-10)	
Stabilizer	On/Off	
Alarm in/out	8 Inputs / 2 Relay Output	
Pan/Tilt angle	360° Endless / 92°	
Pan speed	0,1° ~ 240°/sec (64 Levels)	
Preset point	250 Presets	
Preset speed	Max 360°/sec (64 Levels)	
Privacy zones masking	16 Zones	
Communication system	RS-485 / 422	
Operating Fan/Heater	Over than 45°C / Less than 5°C	
Operating humidity	Less than 90% RH	
Operating temperature	-10°C ~ 50°C (-14°F ~ 122°F)	
Dimensions	215,6mm(Diameter) × 279,6mm(Height)	
Weight	About 5,2Kg (Without adaptor)	
Construction	Aluminum body, Clear vandal bubble (PC)	
Power consumption	21W (Max)	
Power supply	AC24V, 60/50 Hz	

DIMENSIONS

