



## ITC 4S Series

4-Channel Power Amplifier  
T-4S60/T-4S120

T-4S240



### Description

The 4 channel power amplifiers are designed for commercial and industrial public address applications. With four separate amplifier in a single chassis and rated power ranges from 60W, 120W and 240W per channel which provides a wide selection to meet different size sound system needs. The amplifier is design of rack mount type and T-4S60/T-4S120 are in 2U height while T-4S240 is in 3U height.

Balanced line inputs by phoenix types, 100V, 70V and 4-16ohm speaker outputs for each channel by phoenix types are convenient for installation when selection different speaker matching. Master volume controls for each control are included. Complete protection includes peak, short circuit, high temp and overload. Indications for power, signal, peak and protection.

### Features

- 4 separate amplifier into one chassis
- Rack mount amplifier in 2U (T-4S60/T-4S120) and 3U (T-4S240) types.
- Rated power from 60W, 120W to 240W per channel
- 100V, 70V and 4-16ohm speaker outputs for each channel by phoenix types
- Isolated transformer for human safety operation
- Balanced phoenix type line input for each channel
- Reliable protection of peak, short circuit, high temp and overload.
- Indications for power, signal, peak, and protection
- Excellent device of radiator cooling fanner that ensures working effectively.

### Optional

- DC 24V input available on less than but not included 240W models
- Panel with/without handhold
- Faults monitoring module, it can output short circuit signal to achieve main/spare amplifier switch (Except for 1000W and 1500W).



## Public Address & Communication System

### Specifications

Model	T-4S60	T-4S120	T-4S240
Rated Power Output	4 x 60W	4 x 120W	4 x 240W
Speaker Outputs	70V,100V & 4 ~ 16Ω		
Input	775mV/0dB		
Frequency Response	50Hz ~ 15KHz(±2dB)		
S.N. Ratio	Better than 90dB		
THD	Less than 0.5% at 1KHz,1/3 rated power		
Controls	Power switch, volume control		
Indicators	Power, signal, protect and peak LEDs		
Protection	AC fuse, short-circui, clipping and high temperature		
Power Supply	~ 110V/60Hz or ~ 230V/50Hz		
Power Consumption	350W	700W	1500W
Weight	16.8Kg	20.5Kg	26.6Kg
Dimensions	484x490x88mm		484x490x132mm
Finish	Panel:aluminum plate Case:steel plate		