



## Public Address & Communication System

### ITC T-6240B

Pre-Amplifier (XLR MIC + Phantom Power)  
T-6240B



#### T-6240B Descriptions

The T-6240B is covers all features of T-6240, while the differences are the 8 channel inputs, 8 channel outputs and 2 EMC inputs all are in balanced XLR type.

#### T-6240B Features

- 8 balanced line/Mic inputs by XLR type
- 8 balanced line outputs by XLR type
- One Mic input with VOX priority
- Two EMC priority inputs by XLR type
- EMC1 has priority over all inputs (Except MIC 1)
- 2U rack-mount chassis

#### T-6240B Optional

- DC 24V
- Panel with/without handhold

#### Specifications

<b>Model</b>	T-6240B
<b>Input</b>	MIC: 5mV/600Ω, balanced CH1 ~ CH8: 350mV/15KΩ, balanced EMC(1 ~ 2): 350mV/15KΩ, balanced
<b>Output</b>	1V, 600Ω/balanced
<b>Frequency Response</b>	20Hz ~ 20KHz (±2dB)
<b>S/N Ratio</b>	85dB
<b>THD</b>	0.01%
<b>Crosstalk</b>	MIC: 80dB; LINE 85dB; MIC 1 priority
<b>Muting Function</b>	EMC1, 2 overrides other input signals(exception MIC 1) With 0-30dB attenuation
<b>Controls</b>	LINE, MIC controls, channel selectors, power switch
<b>Indicators</b>	Power LED, MIC channel LEDs
<b>Protection</b>	AC fuse: 1A
<b>Power Supply</b>	~ 110V/60Hz or ~ 230V/50Hz, DC 24V optional
<b>Power Consumption</b>	35W
<b>Weight</b>	4.7Kg
<b>Dimensions</b>	484x361x88mm
<b>Finish</b>	Panel: aluminum plate, balck