



Public Address & Communication System

T-205CW

T-206CW

T-208CW



Descriptions

Model	T-205CW	T-206CW	T-208CW
Power Taps @100V	2.5W, 5W, 10W, 20W	3.8W, 7.5W, 15W, 30W	5W, 10W, 20W, 40W
Power Taps @70V	1.25W, 2.5W, 5W, 10W, 20W	1.9W, 3.8W, 7.5W, 15W, 30W	2.5W, 5W, 10W, 20W, 40W
Transformer Impedance	4K Ω /2K Ω /1K Ω /500 Ω /250 Ω	2.6K Ω /1.3K Ω /670 Ω /330 Ω /165 Ω	2K Ω /1K Ω /500 Ω /250 Ω /125 Ω
Input	70V/100V/8 Ω	70V/100V/8 Ω	70V/100V/8 Ω
SPL(1W/1M)	88dB \pm 3dB	89dB \pm 3dB	90dB \pm 3dB
Max. SPL (Rated W/1M)	101dB	104dB	106dB
Frequency Response (-10dB)	100-18KHz	60-18KHz	50-18KHz
Finish	Baffle: ABS, White Cover, Grille: Steel, White	Baffle: ABS, WhiteCover, Grille: Steel, White	Baffle: ABS, White Cover, Grille: Steel, White
Speaker Driver	5" \times 1 1.5" \times 1	6" \times 1 1.5" \times 1	8" \times 1 1.5" \times 1
Cutout Size	171mm	202mm	245mm
Dimensions	202 \times 152mm	233 \times 165mm	275 \times 195mm
Weight	1.4Kg	1.6Kg	2.5Kg
Mounting	Flush-mount dog ears	Flush-mount dog ears	Flush-mount dog ears

Specifications

