



## Public Address & Communication System



### Descriptions

Model	T-774H/T-774HW	T-775H/T-775HW	T-776H/T-776HW	T-778H/T-778HW
<b>Power Taps @100V</b>	2.5W, 5W, 10W, 20W	3.75W, 7.5W, 15W, 30W	5W, 10W, 20W, 40W	7.5W, 15W, 30W, 60W
<b>Power Taps @70V</b>	1.25W, 2.5W, 5W, 10W, 20W	1.9W, 3.75W, 7.5W, 15W, 30W	2.5W, 5W, 10W, 20W, 40W	3.75W, 7.5W, 15W, 30W, 60W
<b>Transformer Impedance</b>	4K $\Omega$ /2K $\Omega$ /1K $\Omega$ /500 $\Omega$ /250 $\Omega$	2.6K $\Omega$ /1.3K $\Omega$ /670 $\Omega$ /330 $\Omega$ /165 $\Omega$	2K $\Omega$ /1K $\Omega$ /500 $\Omega$ /250 $\Omega$ /125 $\Omega$	1.3K $\Omega$ /670 $\Omega$ /330 $\Omega$ /165 $\Omega$ /81 $\Omega$
<b>Input</b>	70V/100V/8 $\Omega$	70V/100V/8 $\Omega$	70V/100V/8 $\Omega$	70V/100V/8 $\Omega$
<b>SPL(1W/1M)</b>	86dB	88dB	89dB	94dB
<b>Max. SPL (Rated W/1M)</b>	99dB	103dB	105dB	112dB
<b>Frequency Response (-10dB)</b>	120-18KHz	100-18KHz	100-20KHz	100-20KHz
<b>Finish</b>	Baffle: ABS, Black/White Grille: Steel, Black/White	Baffle: ABS, Black/White Grille: Steel, Black/White	Baffle: ABS, Black/White Grille: Steel, Black/White	Baffle: ABS, Black/White Grille: Steel, Black/White
<b>Speaker Driver</b>	4" x1 1.5" x1	5" x1 1.5" x1	6" x1 1.5" x1	8" x1 2" x1
<b>Dimensions</b>	276x170x170mm	285x180x186mm	340x220x225mm	450x295x290mm
<b>Weight</b>	2.3kg	2.7kg	4.1kg	6.5kg
<b>Mounting</b>	With mounting bracket fixed by screw	With mounting bracket fixed by screw	With mounting bracket fixed by screw	With mounting bracket fixed by screw

**Specifications**

