



HTDZ

CONFERENCE SYSTEM

Main Unit HT-7000D



1. Equipped with four group of 8P-DIN plugs for system connecting, each unit can support 60 units microphone, it could be extended to support 240 units microphone with extension power supply unit.
2. Digital display and working mode on the panel.
3. Equipped with three buttons to setting the working mode: “Mode/Number/Save.
4. Support many kinds of conference mode: Free mode, FIFO mode, and Limit mode.
 - Open mode: All the delegates can give a speech freely.
 - FIFO mode: first in, first out; first indicators, first offers.
 - Limit mode: MIC1~9 limit
 - Indicative sound for chairman unit (optional)
5. Equipped with the port to support telephone coincidence.
6. Build-in feedback inhibition circuit.
7. Support video camera auto-track with video processor
8. Power consumption: 115W
9. Installed in 19-inch frame.



HTDZ

Microphone Unit HD-3500C/D



- 1) Frequency response: 40Hz-16KHz
- 2) Sensitivity: -44 dB±2dB
- 3) Reference sound receiving distance: 20~120cm
- 4)Support discuss&video
- 5)Chairman with priority button
- 6) Dimension :150mmX120mmX50mm
- 7) N.W. 1kgs

Technical Data

HT-7000D / HT-3500C-D	Main Unit	Microphone Unit
Voltage	AC110~220V/50Hz	DC24V (Supply by 8PIN cable)
Power consumption	115W	2W
T.H.D.	<0.05%	<0.05%
Dimension unit	480X340X90mm	150X120X50mm / MIC pipe 390mm
S/N	> 75db	> 75db
Data Communication	Rj-45	
Sensitivity	-56dB Wire	-44dB ±2dB
Frequency response	100Hz——18KHz	40Hz——16KHz
Color	Grey	Grey
Installation	19-inch unit	Removable