



# HTDZ

## CONFERENCE SYSTEM

### Main Unit HT-7300



1. Power consumption of main unit 400W, each unit can support 60 units delegate and chairman microphone, it could be extended to support 250 units microphone by adding more Extension machines
2. This system can work with computer or without computer. User can select the system manage mode on the front panel of main unit: PC manage mode and main unit manage mode.
3. Main unit has following features when work without computer
  - a. LCD display the working mode on the front panel
  - b. Support many conference work mode: Free, FIFO (1-9 microphone unit), Limit (1-9 microphone unit).
4. Main unit has following features when work with computer and other equipments
  - a. Manage the meeting with software, support double screen display
  - b. Voting function (yes, no abstain)
  - c. Electing function (single-ballot and Multiple-ballot)
  - d. Audience response (100, 75, 50, 25,0)
  - e. Video camera auto-track function
  - f. System can support following discuss work mode: Free mode, FIFO mode (1-9 microphone unit), Limit mode (1-9 microphone unit)
5. With the port for Telephone interface input, telephone meeting is available with telephone coincidence.
6. Power supply: AC220V 50/60Hz
7. Installation:19-inch frame
8. Connection:
9. ---1 pcs 13m main cable with 8PIN plugs.
10. ---8PIN socket for system connection.



# HTDZ

## Microphone Unit HD-7800C/D



- 1) Frequency response: 40Hz-16KHz
- 2) Sensitivity: -44 dB±2dB
- 3) Reference sound receiving distance: 20~120cm
- 4) Portable table moving and microphone pipe can be pull out
- 5) Newly digital design
- 6) LCD display
- 7) Listening and speaking
- 8) The system power supply for all the delegate units is provided by the main unit at 24 safe voltages.
- 9) With 8-PIN T-type hand-in-hand interconnection cable
- 10) Built-in high fidelity speaker and earphone jack.
- 11) Electric capacity type microphone, equipped with windshield cover
- 12) Extended pipe optional.
- 13) The annular red indicator lamp could show the state of the microphone.
- 14) With camera auto-track function
- 15) With voting function (Chairman can control the voting when without computer)
- 16) The chairman unit number in the system is unrestricted, can join in any position of the system.
- 17) Chairman can turn down delegate MIC by priority button,
- 18) Indicative sound for chairman unit (optional)
- 19) C. only mode: only chairman microphone can be turn on.
- 20) Earphone output jack and wireless microphone input jack for chairman unit (optional)
- 21) Dimension :245mmX150mmX60mm
- 22) N.W. 0.7kgs



# HTDZ

## Technical Data

<b>HT-7300 / HD-7800C-D</b>	<b>Main Unit</b>	<b>Microphone Unit</b>
Voltage	AC110~220V/50Hz	DC24V (Supply by 8PIN cable)
Power consumption	400W	2W
T.H.D.	<0.05%	<0.05%
Dimension unit	480X330X90mm	245X150X60mm / MIC pipe 450mm
S/N	> 75db	> 75db
Control port	RS-232 interface	
Sensitivity	-56dB Wire	-44dB ±2dB
Frequency response	40Hz——16KHz	40Hz——16KHz
Color	Grey	Grey
Installation	19-inch unit	Removable