



HTDZ

PROFESSIONAL MICROPHONE

HT-809 Meeting Microphone

- **Capsule Type** : Condenser
- **Frequency Response** :20Hz – 20Khz
- **polar pattern** : Cardioid
- **Output Impedance** : 75Ω
- **Sensitivity** :-40dB
- **Power Supply** :DC 3V/Phantom Power
- **Microphone Length** :445 mm
- **N.W.** :0,69 Kg
- **Sound Pick-up Distance** :45cm
- **Battery working time** :24 Hour
- **Base Dimension(WxDxH)mm** :103x155x32
- **Ouput** :Balance/Mic. Led



HT-909 Meeting Microphone



- **Capsule Type** : Condenser
- **Frequency Response** :20Hz – 20Khz
- **polar pattern** : Super Cardioid
- **Output Impedance** : 75Ω
- **Sensitivity** :-40dB
- **Power Supply** :DC 9V/Phantom Power
- **Microphone Length** :440 mm
- **N.W.** :0,81 Kg
- **Sound Pick-up Distance** :45cm
- **Battery working time** :22 Hour
- **Base Dimension(WxDxH)mm** :100x144x38
- **Ouput** :UnBalance/Mic. Led



HTDZ

PROFESSIONAL MICROPHONE

HT-81A Shotgun Microphone

- **Capsule Type** : Condenser
- **Frequency Response** : 100Hz – 20Khz
- **polar pattern** : Ultra Cardioid
- **Output Impedance** : 1K Ω
- **Sensitivity** : -38dB
- **Power Supply** : DC 1,5V/Phantom Power
- **N.W.** : 0,12 Kg
- **Sound Pick-up Distance** : 3mt
- **Battery working time** : 26 Hour
- **Dimension mm** : Diameter 22,Length 360
- **Ouput** : Balance



HT-320F Condenser Microphone



- **Capsule Type** : Condenser
- **Frequency Response** : 20Hz – 20Khz
- **polar pattern** : Super Cardioid
- **Output Impedance** : 75 Ω
- **Sensitivity** : -40dB
- **Power Supply** : Phantom Power
- **N.W.** : 0,11 Kg
- **Sound Pick-up Distance** : 3 mt
- **Dimension mm** : Diameter 30,Length 170
- **Ouput** : Balance