

BEATISER WP-800



Detailed Product Description

Compact trapezoidal full range 2-way loudspeaker with an 8" low frequency driver and a 1.4" high frequency driver on a Converging Elliptical Waveguide in an easily transportable trapezoidal enclosure. Includes two stage high frequency protection systems to guard against HF driver overload. Constructed from plywood, fitted with flush handles, internal two Speakon NL4MP connectors.

Application,

Live Performance/mobile DJ.

Fixed installations

Model: WP-800

System: 2-way loudspeaker system

Frequency response (± 3 dB): 60Hz~19 KHz

LF driver: DY-A8502x1 (8in) $\Phi 50$ mm voice-coil

HF driver: DH-34Bx1 (1.4in) $\Phi 34$ mm voice-coil

Nominal Impedance: 8ohms

System sensitivity (1w@1m): 95dB SPL

Maximum SPL: 120dB

Power handling: 150W

Peak power: 300W

Nominal Coverage angle (H x V): 60°x 60°

Dimensions (W x D x H): 268x255x460 mm/PCS

Connectors: 2xSpeakon| connectors (NL 4)

Enclosure material: 15mm plywood

Finish: Textured black paint

Grille: Black perforated steel

Suspension system: M8 Screw

Net weight: 10Kg

Shipping size: 333x320x535mm/0.057CBM/PC