



Instruction :

VGA0801 series Matrix Switcher is a high-performance professional VGA signals switcher, used for synchronism switching or cross switching VGA signals and mainly used in broadcast room, multi council-chamber, television teaching room and command center

Features :

- Video Inputs: 15-pin HD female port
- Video Outputs: 15-pin HD female port
- Control Port : RS232, female 9-pin D connector
- Compatible with component video, RGBHV, RGBHV, RGBS, RGsB, RsGsBs, HDTV
- 250 MHz (-3dB) bandwidth, full loaded
- 10 global presets
- Adopting the gain-compensation and synchronization signal proofread technology
- Power-fail protection
- Rack-mountable enclosure
- Video Outputs: 15-pin HD female port
- Universal international power supply (110V-240V)

Parameter:**Video Signal :** RGBHV, RGBS, RGsB, RsGsBs**Connector :** Female15 pin HD**Gain :** 0 dB**Bandwidth :** 250MHz(-3dB),fully load**Video Impedance :** 75Ω**Switching Speed :** 200ns(Max.)**Input/output level :** 0.5V~2.0Vp-p**Control/Remote :** RS-232,9-pin female D connector**Pin configurations :** 2=TX,3=RX,5=GND**Software Control :** Switch 2.0**Temperature :** -20 to +70°C(-20 to 158 F)**Humidity :** 10%~90%**Power supply :** 100VAC~240VAC, 50/60Hz**Power :** 25W**Enclosure Dimensions(mm) :** W482.6XH43.6XD242(1 U high, full rack wide)**Weight :** 2.5kg